



RF-2125

BAS Interchangeable Frequency Module



SPECIFICATIONS

Frequency Range

2025 - 2145 MHz

RF Modulation

OFDM (64QAM, 16QAM, QPSK, BPSK)

Antenna Chains

3 Independent RF Chains

TX/RX Operating Modes

All MIMO modes from SISO to 3x3

Channel Bandwidth

5, 10, and 20 MHz

Software Configurable

Peak TCP Throughput

150 Mbps at 20 MHz Channel

MIMO Techniques

Maximal Ratio Combining

Space-Time Block Coding

Spatial Multiplexing

Max. Aggregate Transmit Power

6W (2W per RF Chain)

Antenna Ports

(3) SMP (50 Ohms)

TX Power Control

33 to 16.5 dBm, 0.5 dB per step

Power Control Accuracy

+/- 2 dB

Frequency Accuracy

+/- 4 ppm, max.

Minimum Receiver Sensitivity

-95 dBm at 5 MHz bandwidth, BPSK

Max. RF Input

-5 dBm, min.

Max. RF Input without Damage

+10 dBm, min.

Max. Peak Power Consumption, TX

30.8W

Power Consumption, RX

4W

Operating Temperature

-40°C to +85°C

ESD Protection

+/- 8KV Contact discharge, per IEC 6100-4-2

+/- 15KV Air discharge, per IEC 61000-4-2

Dimensions

3.8 x 2.6 x 0.5 in.

9.7 x 6.6 x 1.3 cm

Weight

4.6 oz.

130 g

RELEASABLE